



Ref. No. SSM/GEN/02(QT)/24-25

Date 18.06.2024.....

**NOTICE INVITING QUOTATION**

Sealed quotations for PVC Identity Card Printing Machine are hereby invited, from resourceful Benefited Suppliers having credentials in similar type of supply (both in quantitative & qualitative aspect) for College Building.

1. The supply should be completed within 07 days from receipt of formal order.
2. No Earnest Money is required to be deposited along with the quotation.
3. On-spot delivery rate, including carriage and Taxes, should be quoted.
4. The last date of submission of Quotation is 25.06.2024 by 2:00 PM at College Office.
5. That would be opened on 25.06.2024 in front of intending Quotationers.
6. The undersigned reserves the right of accepting Copy forwarded for information and taking necessary action to.



( DR. SABYASACHI SEN )  
Principal

Principal  
Shyampur Siddheswari Mahavidyalaya  
Ajodhya, Howrah.

Category		1	2	3
Printing	Print Type	Dye-Sublimation		
	Resolution	300dpi (Color & Mono), 600 & 1200dpi (Mono only) / Edge to Edge		
	Dual Side Printing	Option (with Flipper)	Yes	Yes (Flipper Installed)
Card	Card Feeding	Automatic		
	Card Size & Thickness	ISO CR80 or ISO CR79 (Option-Factory installed)   0.38mm (15mil) ~ 1.0mm (40mil)		
	Card Type	PVC, PET, Composite PVC		
Print Speed	Monochrome	5 sec./card (720 cards/hour)		
	YMCKO	Front-in & Front-out	Max. 17 sec./card (212 cards/hour)	
		Front-in & Back-out	Max. 16 sec./card (225 cards/hour, Simultaneous)	
	YMCKOK	-	Max. 22 sec./card (164 cards/hour)	
Laminating Speed	Simultaneous (Single Lamination)	YMCK	-	22 sec./card
		YMCKK	-	32 sec./card
	One by One (Single Lamination)	YMCK	-	43 sec./card
		YMCKK	-	53 sec./card
Capacity	Input Hopper	100 Cards / 200 Cards with cover open		
	Output Hopper	Front : 40 Cards / Back : 100 Cards (Optional Back-side Stacker)		
System	Display & Control Panel	2 Line LCD / 2 LED Buttons		
	Supported Platforms	Microsoft Windows 7/ 8 /10, Mac OS, Linux		
	Communication	USB / Ethernet, WiFi (Option)		
	Power Supply	DC 24V		
	Power Consumption	48	48	96
	Temperature/Humidity	15~35° / 35~70%		
Security	Physical Lock	Input Hopper & Ribbon (Option) / Laminate Film (Option)		
	Kensington Lock	Option		
Dimensions	WxLxH (Millimeter / Inch)	165 x 390 x 210 / 6.5 x 15.4 x 8.3	165 x 498 x 210 / 6.5 x 19.6 x 8.3	165 x 675 x 210 / 6.5 x 26.6 x 8.3
	Kg/lbs	4.5 / 10	5.2 / 11.5	8.8 / 19.4
Encoding Option	Magnetic	ISO 7811 (Track I, II, III Read/ Write, HiCo/ LoCo), JIS II		
	Contact	ISO 7816 (ID-1)		
	Contactless	MIFARE, ISO 14443 (Type A/ B), ISO 15693, DESFIRE, iCLASS		
Software		Excel Connectivity Software		

1. The Convener, Purchase Committee.

2. The Office Notice Board, Shyampur Block – II Notice Board, D.M. Ghat – I G.P. Office Notice Board & College Web-site.